Large Scale Real-time Ridesharing with Service Guarantee on Road Networks

Yan Huang #1, Ruoming Jin *2, Favyen Bastani $3, Xiaoyang Sean Wang +4

Computer Science and Engineering, University of North Texas
[1]huangyan@unt.edu

* *Computer Science, Kent State University*
[2]jin@cs.kent.edu

$ *Massachusetts Institute of Technology*
[3]fbastani@mit.edu

\+ *Computer Scicence, Fudan University*
[4]xywangCS@fudan.edu.cn

arXiv:1302.6666v1 [cs.DS] 27 Feb 2013

***Abstract*— The mean occupancy rates of personal vehicle trips in the United States is only 1.6 persons per vehicle mile. Urban traffic gridlock is a familiar scene. Ridesharing has the potential to solve many environmental, congestion, and energy problems. In this paper, we introduce the problem of large scale real-time ridesharing with service guarantee on road networks. Servers and trip requests are dynamically matched while waiting time and service time constraints of trips are satisfied. We first propose two basic algorithms: a branch-and-bound algorithm and an integer programing algorithm. However, these algorithm structures do not adapt well to the dynamic nature of the ridesharing problem. Thus, we then propose a kinetic tree algorithm capable of better scheduling dynamic requests and adjusting routes on-the-fly. We perform experiments on a large real taxi dataset from Shanghai. The results show that the kinetic tree algorithm is faster than other algorithms in response time.**

I. Introduction

Despite our struggle with energy, pollution, and congestion, many private and public vehicles continue to travel with empty seats. The mean occupancy rate of personal vehicle trips in the United States is only 1.6 persons per vehicle mile [1]. In 1999, if 4% of drivers would rideshare it would have offset the increase in congestion in the 68 urban areas completely that year [2]. Several large cities begin to encourage taxi sharing.

Real-time ridesharing [3], [4], [5], enabled by low cost geo-locating devices, smartphones, wireless networks, and social networks, is a service that dynamically arranges ad-hoc shared rides. In a real-time ridesharing with service guarantees on road networks problem (hereafter referred to simply as ridesharing), a set of servers travel over a road network, cruising when not committed to any service and delivering passengers otherwise. Requests for rides are received over time, each consisting of two points, a *source* and a *destination*. Each request also specifies two constraints, a *waiting time* defining the latest time to be picked up and a *service constraint* defining the acceptable extra detour time from the shortest possible trip duration. When a new request is received, it is evaluated immediately by all servers. In order to be assigned the request, a server must satisfy all constraints, both those of the new request and those of requests already assigned to the server. *The goal is to schedule requests in real-time and minimize the servers' traveling times to complete all of the committed service while meeting service quality guarantee*.

The traditional dial-a-ride problem [6] aims at designing vehicle routes and schedules for small to middle sized trip and vehicle sets, e.g. a few vehicles serving tens of requests. Large scale private car sharing and real-time on-demand taxi or cab sharing are becoming increasingly popular. Increasing numbers of users use mobile devices or the Internet to request and participate in these ride-sharing services. Tickengo [3], founded in 2011, is an open ride system where over 50,000 people participate in ridesharing. Other companies include Avego, PickupPal, Zimride, and Zebigo. In an urban city like Shanghai, there are approximately 120,000 road intersections, 40,000 taxis, and more than 400,000 taxi trips per day (these numbers are derived from our experimental dataset). Slight change of weather such as light rain will send the city into a gridlock. With the mounting energy, pollution, and congestion problems in the urban and metropolitan areas that are growing at tremendous rates and already host more than half of the entire human population, trading a small amount of privacy and convenience for energy and cost savings using ridesharing is promising and maybe inevitable.

However, providing ridesharing service at the urban scale is a non-trivial problem. The core is to devise a real-time matching algorithm that can quickly determine the best vehicle (taxi, cab, bus) to satisfy incoming service requests. Traditional solutions to the related dial-a-ride problems using branch-and-bound [7] or mixed integer programing [8] approaches are not designed to deal with these enormous modern situations. Furthermore, most previous solutions focus on scenarios where requests are known ahead of time and servers originate and finish at known depots. The dynamic and en route nature renders many of these algorithms either inapplicable or inefficient.

In this paper, we focus on developing fast matching algorithms for large scale real-time ridesharing. Our algorithms are applicable to the existing services including taxi services,

private vehicle sharing, elevator systems, minibus services, and courier services. We note that there are other important factors which need to be considered for the emerging large scale real-time ridesharing, such as inter-personal (female vs. male), safety, social discomfort, and pricing concerns. Those can be addressed by real-name profiling, reputation, or social network trust building systems [4], [1] and beyond the scope of this paper.

A. Problem Definition

A road network $G =< V, E, W >$ consists of vertex set V and edge set E. Each edge $(u, v) \in E$ $(u, v \in V)$ is associated with a weight $W(u, v)$ which indicates the traveling cost along the edge (u, v); this traveling cost can be either a time measure or a distance measure. Assuming driving speeds are available, time measure and distance measure can often be converted from one to another and are used interchangeably.

Given two nodes s and e in the road network, a path p between them is a vertex sequence $(v_0, v_1, \cdots, v_k)$, where (v_i, v_{i+1}) is an edge in E, $v_0 = s$, and $v_k = e$. The path cost $W(p) = \sum W(v_i, v_{i+1})$ is the sum of each edge cost $W(v_i, v_{i+1})$ along the path. The shortest path cost $d(s, e)$ is defined as the minimal cost for paths linking from s to e, i.e., $d(s, e) = \min_p W(p)$ and the corresponding path with cost $d(s, e)$ is the shortest path from s to e.

Definition 1: (**Trip Request**) A trip $tr =< s, e, w, \epsilon >$ with respect to a road network $G =< V, E, W >$ is defined by a source $s \in V$, a destination $e \in V$, a maximal waiting time w (defines the maximum time allowed between making the request and receiving the service), and a service constraint ϵ for the extra detour time in a trip (bounding the overall distance from s to e by $(1 + \epsilon)d(s, e)$).

We consider a unified waiting time w and service constraint ϵ for all requests, which can be specified by the service provider. However, our proposed algorithms can be easily generalized to individualized waiting time and service constraints. We further assume that G is static over time (i.e., we do not consider different path costs at different times of the day), but the algorithms we present can handle the case where G changes under a predetermined course, and can be extended to the case where G changes unpredictable (for example, to simulate dynamic traffic conditions).

To deal with real-time ride sharing, for each trip $tr_i =< s_i, e_i, w, \epsilon >$ and a given server (e.g., a taxi, cab, or private vehicle), we further introduce r_i, the server's location when the request is made. Given this, a general *trip schedule* for a server with m trips can be described in a sequence with $3m$ elements, $(x_1, x_2, \cdots, x_{3m})$, where an element x_j in the sequence is either a trip source (s_i), a trip destination (e_i), or trip request point (r_i). Furthermore, a server is assumed to travel along the shortest path in the road network when moving between any two consecutive points in the trip schedule x_i and x_{i+1}. Thus, the *trip cost* between any two points (x_i, x_j) in the trip schedule $d_T(x_i, x_j)$ is denoted as

$$d_T(x_i, x_j) = d(x_i, x_{i+1}) + d(x_{i+1,i+2}) + \cdots + d(x_{j-1}, x_j).$$



Fig. 1. Trip Schedule. s_i: trip starting point; e_i: trip ending point; r_i server location when request of trip tr_i comes in; (t, l) is the current time and location of the server.

The overall trip cost is simply $d_T(x_1, x_{3m})$.

Figure 1 illustrates a trip schedule for four trip requests. Note that since each moving server is associated with a trip schedule at any give time, we associate two variables (t, l) with a trip schedule to facilitate our discussion, where t is the current time and l is the current location of the server. Intuitively, if a trip schedule is being executed by a server, (t, l) will move along the trip schedule. Note that, at any given time t, each server is associated with a subset of *active trips*, the trips whose requests have been accepted (with some picked up and some not) but not yet dropped off. For instance, in Figure 1, the active trips are $\{tr_1, tr_2, tr_3\}$ at time t_1; $\{tr_1, tr_2, tr_3, tr_4\}$ at time t_2; and $\{tr_1, tr_2, tr_4\}$ at time t_3.

However, not all the trip schedules can meet the service quality guarantees for each of the individual trip request. We formally introduce the concept of a *valid trip schedule*.

Definition 2: (**Valid Trip Schedule**) A valid trip schedule S for a trip set $TR = \{tr_1, tr_2, \ldots, tr_m\}$ satisfies three conditions:

1) **Point order** For any trip tr_i, let $x_{i1} = r_i$, $x_{i2} = s_i$, and $x_{i3} = e_i$, then, $i_1 < i_2 < i_3$, i.e., the requesting point must happen before the pickup point, which must happen before its ending point;
2) **Waiting time constraint** For any trip tr_i, the distance (waiting time) from the server's location when the request is made to the request's pickup point should be smaller than the waiting time constraint, i.e., $d_T(r_i, s_i) \leq w$;
3) **Service constraint** For any trip tr_i, the actual travel distance from the pickup point to the dropoff point $d_T(s_i, e_i)$ should be smaller than or equal to the shortest distance between them multiplied by the service constraint, i.e., $d_T(s_i, e_i) \leq (1 + \epsilon)d(s_i, e_i)$.

To formally define the *real-time ridesharing* problem, we further introduce the *augmented valid trip schedule*: *Assuming at time t, there are m active trips for the given server, let the current valid trip schedule be $(x_1, x_2, \cdots, x_{3m})$, where (t, l) is between x_i and x_{i+1}. For a new trip request tr_{m+1}, the augmented valid trip schedule shall be $(x'_1, x'_2, \cdots, x'_{3m+3})$, where $x'_j = x_j$ for $j \leq i$, and $x'_{i+1} = r_{m+1}$.* In other words, the augmented valid trip schedule combines the new request with the existing requests and shares the same partial trip schedule before the new request is made at time point t. Also any augmented valid trip schedule consists of two part: the *finished schedule* $(x_1, x_2, \cdots, x_i, r_{m+1})$ and the new *unfinished schedule* $(r_{m+1}, x'_{i+2}, \cdots, x'_{3m+3})$.

The problem of **Real-Time Ridesharing** *is: Given a set of*

vehicles on the road network G and a new incoming request tr, find the vehicle that minimizes the overall trip cost for the augmented valid trip schedule.

Note that since the finished schedule part in the augmented valid trip schedule cannot be changed (because it has already been executed), we essentially need to find the minimal trip cost for the new unfinished schedule part which includes m active trips and a new trip request. We also observe that the minimal cost is for helping determine the best match between the incoming trip request and the available vehicles in a real-time fashion. The minimal cost, then, is greedy in nature: When additional new requests comes in, the past optimal choice matching between the current trip request and the server may not be the minimal anymore. However, in the real-time request, this type of optimality tends to be the best we can achieve as the future requests are not available and can be rather easily understood and accepted by riders.

Finally, we note that the problem of real-time ridesharing is NP-hard as the classical Hamiltonian path problem can be reduced to this problem (assuming all the trips have the same ending points and requested in almost the same time). For simplicity, the details of NP-hardness is omitted here.

B. Challenges

The main challenge in ridesharing is to determine how to handle trip requests as they flow into the system in real-time. From a server's point of view, for any new request, each server may have already selected (and be executing) a trip schedule for its existing customers. Given this, how can we quickly help it to determine whether it can accommodate a new request? Note that in order to respond to such a request, one may have to reshuffle the predefined schedule and the reshuffled one has to be a valid schedule.

Furthermore, there might be tens to even hundreds of servers in the region surrounding the pickup point of a new request. Clearly, for a trip request tr_i, servers that are farther than w from the pickup location are unable to respond to the request. Thus, we can already reduce the potential candidates to only those that are within w of the pickup point. Then, the customer will be assigned to the server that offers the shortest total trip time. Even though potential servers can be filtered through a dynamic spatial indexing structure [9], [10], [11] on the moving servers, the existing approaches can still be very computationally expensive and result in low response times. In a large metropolitan area such as Shanghai, the number of requests can be very large, especially during rush hour.

Most algorithms are designed for offline computation. The existing approaches that use branch-and-bound [12] or integer programing [8] to schedule new requests do not take the dynamic nature of the problem into consideration. Testing if a new request can be accommodated essentially involves a rescheduling of the unfinished trips and the new request without reusing the computations in the previous round. Their calculation time was measured in minutes or hours while we require milli-second response time.

C. Contributions

To deal with the challenges, our idea is based on a simple observation. For a new valid schedule accommodating the new request tr_i, if we simply drop the three points r_i, s_i, e_i from the trip schedule, then the resulting trip schedule is a valid trip schedule. In other words, only a valid trip schedule can be extended to accommodate a new request. Given this, a potential approach for the ridesharing problem is to simply materialize every valid trip schedule; then, when a new request arrives, we can check if any valid trip schedules can be extended to handle the new request. This approach is promising because its incremental nature saves many redundant computations: We do not need to recompute the valid trip schedule completely from scratch on each new request. However, in order to implement such a strategy, we have to deal with the following challenges: 1) Would the materialization incur too much memory cost? In other words, can we store the materialized schedules compactly? 2) How can we efficiently maintain the materialization? Note that when the server moves, the materialization needs to be updated. 3) How can the materialization help to test quickly whether a new request can be handled? 4) How can the materalizaton be updated when a new requested is accepted?

This paper makes the following contributions:

- We formulate the ridesharing problem in a way that resembles the scenario enabled by current locating and communication technology; We propose a kinetic tree approach for the matching problem. The tree structure lends itself naturally to the dynamic nature of the problem;
- When the pickup or dropoff locations are close to each other, any permutation of the locations can be valid, rendering the constraints ineffective and resulting in a large number of valid schedules. We propose a hotspot-based algorithm that ignores schedules that are almost duplicates to effectively reduce the number of valid schedules while providing a bound on the error for the solution under certain conditions;
- We compare our approach to the branch-and-bound and mixed integer programing approaches that are traditionally used together with the brute-force algorithm. Experiments on a large shanghai dataset show that the tree algorithm is several times to a magnitude faster in response time. We further test tree algorithm on various larger problems to show its performance and effectiveness of the optimizations proposed.

D. Outline

We first describe a branch-and-bound an mixed-integer programming algorithm to solve the problem in Section II. We then propose the kinetic tree approach in Section IV. In section V, we deal with the issue of large trees using a hotspot-based algorithm. Experiment results are presented in Section VI. we discuss related work in Section VII, and present our conclusions in Section VIII.



Fig. 2. Illustration of Branch-and-Bound Algorithm. (1) When request r_2 comes, only $\{e_1, s_2, e_2\}$ need to be scheduled; (b) Road network distance and minimal incident edge cost; (c) When (r_2, e_1, e_2, s_2) with cost 6 is found, partial schedules with estimated costs above 6 are terminated.

II. Branch-and-Bound and Mixed Integer Programming Algorithms

The brute-force algorithm to find the augmented valid trip schedules is straightforward. We enumerate all of the permutations and then check the constraints. However, this can be expensive. Two traditional approaches that are often used in solving the related dial-a-ride problem [6] can increase execution speed: a branch-and-bound algorithm [7] and an integer programming approach [8]. We first propose a modified branch-and-bound algorithm for our problem, and then formulate the problem as a mixed-integer programming problem.

III. Branch and Bound Algorithm

The branch-and-bound algorithm systematically enumerates all candidate schedules and organizes the candidates into a schedule tree. It estimates and maintains a lower bound of each partially constructed schedule and stops building candidate schedules that have lower bounds greater than the best solution found so far. The algorithm first expands the partial candidate with the lowest lower bound (best first search).

Assume at time t, there are m active trips for the given server. Let the current valid trip schedule be $(x_1, x_2, \cdots, x_{3m})$, where (t, l) is between x_i and x_{i+1}. For a new trip request tr_{m+1}, we need to re-schedule the pickup and dropoff points $N = \{x_{i+1}, x_{i+2}, \cdots, x_{3m}, r_{m+1}, s_{m+1}, e_{m+1}\}$. We treat N as a complete graph with vertices being N and edge weights being the shortest path distances between nodes. We attempt to find the schedule through the graph that passes through each node once but, unlike a tour, does not return to the first node. The schedule also has to begin at the location of the server l (this is also r_{m+1}). In Figure 2 (a), when request r_2 comes in, s_1 is already picked up. So, only $N = \{e_1, s_2, e_2\}$ needs to be scheduled and the schedule must start from r_2.

We start with the initial schedule tree $ST =< r_{m+1} >$, and initialize the cost of the optimal schedule to ∞. We then iteratively perform a best-first-search to expand the partial schedule $S =< r_{m+1}, x'_{i+1}, x'_{i+2}, \cdots, x'_k >$ with the minimum lower bound. The key to a branch-and-bound algorithm is to find an effective lower bound. The bound we use is $d_T(r_{m+1}, x'_k)$ plus the sum of the minimum-cost-edge incident to the nodes that are not yet in the partial schedule S.

Figure 2 (b) shows road network costs between two nodes. The minimal incident edge cost is labeled beside each node. In Figure 2 (c), for each node x, the two numbers in a parentheses indicate the cost $d_T(r_2, x)$ of the partial schedule and the lower bound of the schedule containing the partial schedule as prefix. For (r_2, e_1), $d_T(r_2, e_1) = 3$. Only e_2 and s_2, both with minimal incident edge cost of 1, need to be added to the schedule, so the lower bound of a schedule containing (r_2, e_2) is $d_T(r_2, e_2) + 1 + 1 = 5$.

We attempt to expand the partial schedule S with minimal lower bound by another new node to construct S'. If S' is not valid or results in a bound greater than the current minimum schedule cost, we terminate S'. If S' is a complete schedule, we compare its cost to that of the best schedule and update if necessary. Figure 2 (c) shows the execution figure 2 (a) . Once the schedule of cost 6 is found, schedules with lower bounds above 6 can be pruned (labeled by a gray circle). Note that in the figure we do not illustrate validity constraints. The complexity of the branch-and-bound algorithm in the worst case is still exponential.

A. Mixed-integer Programming Approach

Mixed integer programing is a popular alternative. In this section, we formulate our augmented valid trip schedule problem into a mixed integer programming problem. Then, we apply traditional solvers to find the solution.

As in the branch and bound algorithm, we are rescheduling $N = \{x_{i+1}, x_{i+2}, \cdots, x_{3m}, r_{m+1}, s_{m+1}, e_{m+1}\}$. The schedule must start from r_{m+1}. We divide N into subsets: (1) dropoff locations of those already picked up but not dropped off; let the size of this set be k; (2) pickup locations of trips not started yet; let the size of this set be n; and (3) dropoff locations of trips not started yet; the size of this set is also n. The problem can be defined on a complete directed graph $G = (N, A)$ where $N = D' \cup P \cup D \cup \{0\}$, $D' = \{1, 2, \ldots, k\}$, $P = \{k+1, k+2, \ldots, k+n\}$, $D = \{k+n+1, k+n+2, \ldots, k+2n\}$. Here we assign an integer to each point in N while node 0 represents the current position l/r_{i+1} of the server. For a pickup i in P, its matching dropoff in D is $i+n$. A pickup constrain l_i is associated with a node $i \in P$, representing the latest time that node i need to be picked up. Each arc $(i, j) \in A$ are associated with a shortest path routing cost d_{ij}. For each arc (i, j), let $y_{ij} = 1$ if the server travels from node i to node j. For each drop point $i \in D' \cup D$, let L_i be the ride time of the request with dropoff $i \in D' \cup D$ in this partial route.

$$Min \sum_{i \in N} \sum_{j \in N} d_{ij} y_{ij}$$

subject to:

$$
\begin{aligned}
& y_{ij} \in \{0,1\}, && \forall i \in N, j \in N && (1)\\
& \textstyle\sum_{j \in N} y_{ji} = 1, && \forall i \in N - \{0\} && (2)\\
& \textstyle\sum_{j \in N} y_{0j} = 1 && && (3)\\
& B_0 = 0 && && (4)\\
& B_j \geq (B_i + d_{ij}) y_{i,j}, && \forall i \in N, j \in N && (5)\\
& L_i = B_i - B_{i-n}, && \forall i \in D && (6)\\
& B_i \leq w_i, && \forall i \in P && (7)\\
& B_i \leq r_i, && \forall i \in D' && (8)\\
& d_{i-n,i} \leq L_i \leq \epsilon_i, && \forall i \in D && (9)
\end{aligned}
$$

where w_i is the waiting time left for $i \in P$ and r_i is the maximal riding time left for $i \in D'$. Here d_{ii} is set to a positive number to make sure $y_{ii} = 0$.

The objective is to find the schedule that minimizes the total cost while satisfying the constraints. Constraint (1) simply enforces the binary nature of y_{ij}. Constraint (2) allows exactly one node preceding another for all nodes but 0. Constraint (3) allows exact one node following node 0. These two effectively enforce the schedule structure so that each node is visited exactly once and the schedule starts from node 0.

Constraints (4) and (5) set the earliest time at which a node can be reached. Constraints (6) define L_i for dropoff nodes, the service distance. Constraints (7) and (8) enforce the waiting time and service constraints for pickup and dropoff nodes where the passenger has already been picked up. These are grouped together because both w_i and r_i are measured from the root node. Constraint (9) enforces the service constraint for dropoff nodes where the passenger has not yet been picked up, so that the service time does not exceed ϵ_i.

The constraint (5) is not linear. It can be linearized by introducing constants M_{ij} using the idea similar to the Miller-Tucker-Zemlin subtour elimination constraints for the traveling salesman problem [13]:

$$B_j \geq B_i + d_{ij} - M_{ij}(1 - y_{ij}), \forall i \in N, j \in N \qquad (1)$$

The validity of these constraints are ensured by setting $M_{ij} \geq \max\{0, l_i + d_{ij} - e_j\}$ where l_i is the latest time that i need to be served and e_j is the earliest time that j needs to be served. For $i \in P$, $[e_i, l_i] = [d_{0i}, w_i]$. For $i \in D, [e_i, l_i] = [d_{0,i-n} + d_{i_n,i}, w_i + d_{i-n,i}(1+\epsilon)]$. For $i \in D', [e_i, l_i] = [d_{0i}, r_i]$.

Let v be the number of variables in the mixed-integer programming problem, and c be the number of constraints, then $v = O(m^2)$ and $c = O(m)$, where m is the total number of requests that we are optimizing.

IV. Kinetic Tree Approach

The two approaches above both suffer from one fundamental problem: they essentially reschedule the unfinished pickups and dropoffs with the new request from scratch without reusing the computations performed before. The structure of the two algorithms make it difficult to adapt to the dynamic nature of the problem. In this section, we introduce a kinetic tree structure that can maintain and update the calculation performed up-to-now and use them effectively when a new request is issued. However, when there are multiple pickup or dropoff locations close to each other, the possible number of schedules inevitably increase in an exponential fashion. We then propose a hotspot-based approach in section V that reduces the search space and approximates the solution with bounds.



Fig. 3. Kinetic Tree for Trip Schedules. Darkened path: selected schedule to be executed; Dark circled/squared nodes: finished nodes.

A. Basic Tree Structure

We introduce a kinetic tree structure to maintain all the valid trip schedules with respect to the server's current location. When the server moves, a portion of the schedule becomes obsolete. The root of the tree tracks the current location l of the server. The rest of the tree records the portion of all the valid schedules (from the current location onwards).

For a given w and ϵ, Figure 3 illustrates the kinetic tree structure corresponding to the complete trip schedule in Figure 1. The darkened path represents the selected schedule to be executed by the server. Initially, for the first trip request, there is only one valid trip schedule (Figure 3 (a)). When the second request arrives, the first customer has already been picked up by the server. Now, consider there are only two valid options for the server to accept the new request: it needs to first pick up the second customer, but it can be flexible in dropping off either of the two passengers. Let us assume it decides to choose the shorter one which is (l, s_2, e_1, e_2), to drop off the first customer first (assuming the option which drops the first passenger before picking up the second one is invalid). However, on its way to pick up the second customer, the third request arrives. The server now has the options to either pick up the second customer or the third one. Suppose,

consequently, based on w and ϵ, that there are five possible valid trip schedule for the server to handle the three trip requests (trip one is already in progress, shown in Figure 1(c)). Assuming the server decides to move along the shortest route $(l, s_2, s_3, e_3, e_2, e_1)$ for now and picks up the second customer first, then when the fourth request arrives after the pickup of the second customer, the entire right subtree of r_3 in Figure 1(c) becomes inactive. Let us now assume there are only two possible schedules to accommodate the remaining trips of all four customers as shown in Figure 1(d).

Why is such a kinetic tree useful in maintaining the valid trip schedules? Its advantage is based on the the following key observation:

Lemma 1 (Valid Schedules under Movement): When a server reaches a new pickup location or dropoff location in the trip schedule, then only those valid schedules which contain unfinished trips and share the same prefix so far (from the first pickup point of all the unfinished schedules to the current location in the trip schedule) need to be materialized. All the other schedules will become inactive and can be pruned from the tree.

For example, in Figure 3(c), once the server actually picked up the second customer, only the schedules in the left subtree rooted with s_2 remain active. There are two options to perform the tree pruning. The *eager invalidation* option tries to determine whether some trip schedules become inactive as early as possible. In other words, it tries to perform the pruning as the server moves or when the next point in the scheduled route is reached. The *lazy invalidation* option only performs such pruning when necessary, i.e., only when there is a new incoming request.

B. Handling a New Request

Now, we consider how to handle a new request $tr_k = (r_k, s_k, e_k)$. The assumption is that we already have a materialized prefix tree of all valid and active schedules of unfinished trips. Now, we need to extend all valid and active schedules in the prefix tree to a new valid schedule to include tr_k if possible. We do this by generating a new prefix tree based on the existing one. To deal with the new request, we will first deal with the pickup location s_k and then the dropoff location e_k. Essentially, we need to scan the tree to determine where s_k can be inserted, i.e., which edges of the tree can accommodate the insertion of a new pickup node. All schedules that share the prefix from the root of the tree to the inserted edge will be inserted into the new tree. Then we insert e_k after s_k in the new tree. Furthermore, if s_k or e_k can be inserted at a given location (an edge in the tree), then we have to find out which trip schedules containing that edge with an additional node will become invalid and should be pruned from the new tree. The problem is how to determine 1) at which edge s_k or e_k can be inserted, and 2) how to quickly prune the invalid trip schedules following that insertion.

Inserting Pickup Location: Here, we focus on whether s_k can be inserted first and e_k can be inserted in a similar way later. In order to insert s_k in a tree edge, say (x_i, x_{i+1}), we need to deal with the following situations: (a) only when the distance from the current location (recorded in the root node l) to the pickup location s_i satisfies $d_T(l, s_i) = d(l, x_1) + d(x_1, x_2) + \cdots + d(x_i, s_k) \leq w$, then s_k may be inserted; (b) the additional travel distance (time) introduced by the detour to s_k may invalidate some existing trip schedule in the subtree containing this tree edge (x_i, x_{i+1}), i.e., $d(x_i, s_k) + d(s_k, x_{i+1}) - d(x_i, x_{i+1})$ should not be too large. These schedules should be pruned from the subtree. Note that condition (a) is easy to be tested in the existing tree structure.

Lemma 2: $(d_T(l, s_k) \leq w)$ The shortest distance from the current location to the requested pickup location s_k is no larger than w. Furthermore, given a prefix (partial) trip schedule from the root node l to a node x_j, i.e., $(l, x_1, x_2, \cdots, x_j)$, if $d_T(l, s_k) = d(l, x_1) + d(x_1, x_2) + \cdots + d(x_j, s_k) > w$, then, any edge incident to any descendant of x_j in the tree cannot accommodate s_k, i.e., customer can not wait for server until it finishes x_j to pick him up at s_k.

This lemma suggests that we can perform either a depth first search (DFS) or breadth first search (BFS) starting from the root node of the tree to generate all the candidate edge (x_i, x_{i+1}) to insert s_k. Specifically, during the traversal the visiting will return once certain depth is reached, i.e., a node has the property that $d_T(l, x_j) > w$, then, we either will not expand that nodes (in BFS) or trace back (in DFS).

Now the key problem is how to handle condition (b). The straightforward way to perform pruning is to explicitly maintain and check the constraints for each trip request in the subtree of the node x_i. Specifically, for a trip tr_j in the subtree rooted at x_i, there are two criteria: pickup waiting constraint $[r_j, s_j, w]$ $(d_T(r_j, s_j) \leq w)$ and trip tolerance constraint $[s_j, e_j, \epsilon]$ $(d_T(s_j, e_j) \leq (1 + \epsilon) d(s_j, e_j))$. At any given time point t, clearly if we need to test whether the detour meets the criteria of trip tr_j, then the request is already issued and responded, and the entire trip is not yet completed. Further more, only one of the criterion needs to be tested: if the server has not picked up the customer, then, we need to test the pickup waiting constraint $[r_j, s_j, w]$; once the customer is picked up, we need test the trip tolerance constraint $[s_j, e_j, \epsilon]$. Thus, at any given point, the "active" customers can be partitioned into two sets: S_1 records those customers who need to be picked up and S_2 records the on-board customers who need to be dropped off. When a new location is reached, we may move customers from S_1 to S_2 and/or remove customers from S_2. For trip j in S_1, we test the first criterion $[r_j, s_j, w]$ and in S_2, we test the second one: $[s_j, e_j, \epsilon]$. Given this, for the subtree rooted at x_i, the straightforward way is to first generate these two sets S_1 and S_2. Then, when we insert s_k, we need test each condition associated with S_1 and S_2 are also satisfied.

Algorithm 1 implements the insertion of a new request $tr_k = (s_k, e_k)$ into the tree recursively. The insertion is

Algorithm 1 insertNodes algorithm.

Parameter: root node l, request points $P = (x_1, x_2, ...)$, current depth $depth$
  if $feasible(l, x_1, depth + d(l, x_1))$ **then**
    Initialize $fail = 0$
    $n = create(l, x_1)$ {Copy feasible child branches underneath n}
    for each c such that edge (l, c) exists **do**
      $copyNodes(n, \{c\}, d(l, n) + d(n, c) - d(l, c))$
      If copy failed, set $fail = 1$
    end for{Insert remaining request points to n}
    if $fail = 0$ and $|P| > 1$ **then** {Detour now begins negative because we haven't inserted x_2 yet}
      $insertNodes(n, \{x_2, ...\}, -d(x_1, x_2))$
      If insert failed, set $fail = 1$
    end if{Now insert request points into children}
    for each c such that edge (l, c) exists **do**
      $insertNodes(c, P, detour + d(l, c))$
      If insert failed, delete (l, c)
    end for
    if $fail = 0$ **then**
      Add edge (l, n)
    else if No nodes c with edge (l, c) exist **then**
      Insert failed, notify caller that this subtree is infeasible
    else
      Insert succeeded
    end if
  else
    Insert failed, notify caller that this subtree is infeasible
  end if



Fig. 4. Tree Insertion. The insertions of s_3 into each edge in tree of (a) result in new trees in (b), (c), (d), and (e), assuming the last two insertions were infeasible.

completed by a call, $insertNodes(root, \{s_k, e_k\}, 0)$. The call to $feasible(parent, node, detour)$ returns whether or not it is feasible to insert $node$ as a child under $parent$ in the tree. First, this ensures that the pickup or service constraint of $node$ is not violated. If min-max filtering is in place (will be discussed in next section), this will confirm that the detour (third argument) is tolerable for $node$.

The $copyNodes(node, source, detour)$ function recursively copies nodes from a set of nodes, $source$, to the target node, $node$. Here, tolerance of the root's children in $insertNodes$ is implemented through calls to $feasible$ with detour of $detour$. $copyNodes$ will fail if all of the children of $node$ are along infeasible paths. In this case, these branches and $node$ will be deleted.

In Figure 4 (a), we use the insertion algorithm to insert the pickup location s_3 into an existing tree, thereby generating a new tree. s_3 will first be inserted directly below r. Then, the branch with root at s_2 will be copied underneath this new s_3 node, forming a new tree of $(l, s_3, s_2, ((e_1, e_2), (e_2, e_1)))$ is generated. Let us assume route (l, s_3, s_2, e_1, e_2) is not feasible; then, the branch is pruned from the tree starting at the leaf node until we reach s_2, where we have an alternate path $l, s_3, s_2, e_2, e_1)$ that is feasible. This pruning occurs in the $copyNodes$ algorithm, which will succeed because s_3 falls along at least one (in this case, exactly one) feasible path. The resulting tree is shown in Figure 4 (b).

Then, the insertion algorithm moves down to s_2 and attempts to insert the pickup location after it. Two paths are formed: (l, s_2, s_3, e_1, e_2) and (r, s_2, s_3, e_2, e_1), as a result of the insertion between s_2 and e_2 and between s_2 and e_1. The resulting tree is shown in Figure 4 (c). Suppose inserting s_3 between e_1 and e_2 or between e_2 and e_1 is infeasible. Then, we have the tree in Figure 4 (d). To complete the insertion of the (s_3, e_3), we now try to insert e_3 in the subtrees that root at a s_3 following the same insertion algorithm. Once this completes, we arrive at the tree shown in Figure 4 (e).

Min-max Filtering using Slack time: Though the above test for condition (b) is conceptually simple, it is rather computationally expensive. Now, we introduce a fast approach to simplify and speedup such test. For any node j, if j is in S_1, let $\delta_j = w - d_T(r_h, s_j)$; otherwise ($j$ is in S_2), let $\delta_j = (1 + \epsilon)d(s_j, e_j) - d_T(s_j, e_j)$. Then, for the node x_j, we associate **slack time** $\Delta_{x_j} = \min(\delta_j, \max_{i \in x_j.children} \Delta_i)$.

Note that Δ_{x_j} essentially represents the minimal allowed detour on the most "lenient" route of the subtree routed at x_j. Here "lenient" means the route can tolerate the most detour compared to other routes. Given this, we introduce the following Theorem to describe the simple condition to determine whether s_k can be inserted at a given edge.

Theorem 1: For a trip request tr_k, if edge (x_i, x_{i+1}) does not satisfy either of the following condition: (a) $d_T(l, s_k) = d(l, x_1) + d(x_1, x_2) + \cdots + d(x_i, s_k) \leq w$; or (b) $d(x_i, s_k) + d(s_k, x_{i+1}) - d(x_i, x_{i+1}) \leq \Delta_{(x_i, x_{i+1})}$, then, we can not add the pickup s_k between location x_i and x_{i+1}.

After insertion in (x_i, x_{i+1}), the all nodes under x_i of the new tree will be tested for the constraint $\delta_i \geq d(x_i, s_k) + d(s_k, x_{i+1}) - d(x_i, x_{i+1})$. A branch is

pruned from the subtree if the constraint is not satisfied.

Updating Δ and Tree: After we try to insert a request to all possible servers, we get a set of new trees. For each tree, we can find the shortest route and choose the tree what provides the shortest route among all trees. Only the chosen tree needs to have its Δ updated. This can be done through one tree traversal. When a server is moving, the tree needs to be updated as well. However, the Δ values are quiescent to server movement and do not need to be updated. The tree is updated as:

- Vehicles follow their routes and update the server when a new pickup or dropoff location is reached; Server drops the inactive portion of the tree accordingly;
- Many moving object indexing methods have been proposed that includes RUM-tree, TRP-tree, Bx-tree, Bdual-tree, and STRIPES. Indexing can substantially decrease the searching of the candidate taxis. However, a trade off needs to be made between maintaining a complex and search-efficient index and relying on a search-approximate but easy to maintain index. In our dataset, around 1,7000 taxis update their locations every 20 to 60 seconds. We choose to use a simple grid-based spatial index. The index is updated when a vehicle moves across boundaries of the index bounding box. For each request, it identifies the vehicles possibly within w of the request, asks the vehicle's actual location, and then tests if these vehicles can accommodate the request.

V. Hotspot Based Optimization

The main problem with the basic tree algorithm is the exponential explosion of the size of the tree when there are multiple pickup or dropoff locations close to each other. For example, if we have 8 pickups occur in spatial proximity around similar time. e.g airport terminals, any permutation of the pickups may result in a valid schedule. So there are 8!= 40,320 possibilities already without considering the dropoff points. We propose an approximation approach with bound to reduce the search space. The idea is that when the time and space requirement of computing the best schedule are too much, a server may decide to shed the load by only maintaining a subset of the schedules. Since the number of leaves of the kinetic tree is determined by the number of possible routes, the tree size is effectively controlled by the approximation and the service contraints.

We propose the following **hotspot clustering algorithm** to deal with this situation. When we insert a pickup point s_k to an edge (x_i, x_{i+1}), we check if $d(x_{x+i}, s_k) \leq \theta$ where θ is a small number. If so, s_k is inserted into the node of x_{i+1}. s_k and x_{i+1} are treated as one point called *hot spot* in the tree and an arbitrary schedule is chosen among the points in a hot spot. When the hot spot contains more than one point, the newly inserted point needs to be within θ to all the points of the hot spot. Similar procedure can be done for the dropoff points and the mixture of pickup and dropoffs. Once the point



Fig. 5. Bound for Hotspot. x_i, x_j, and x_k are in one hotspot. Black lines: optimal schedule S_{best}. We can convert S_{best} by connecting x_i, x_j, x_k consecutively first and then thread the other locations (represented by ovals). The new schedule has a bounded cost.

is combined with any node, we stop trying to insert it to any other edges.

Let us first assume the service constraints are sufficiently large that all schedules are possible. For a trip set TR, let S_{best} be the optimal schedule. Suppose there is a hotspot hp among the pickup and dropoff locations of TR. Our hotspot-based method chooses an arbitrary schedule T_{hs} that goes through the points of the hotspot in a consecutive manner. We want to prove that the cost of T_{hs} is bounded.

Theorem 2: $cost(T_{hs}) \leq cost(S_{best}) + 2(m+1) \times \theta$ where m is the number of points in the hotspot without considering constraints.

Proof Sketch: We prove when $m = 3$ by illustration. For general m, the proof is mainly the same. In Figure 5 (a), assume $\{x_i, x_j, x_k\}$ has pairwise distance of no greater than θ. The optimal schedule S_{best} is labeled by black solid and dashed lines. We can convert S_{best} into T_{hs} by connecting x_i, x_j, x_k consecutively first and then thread the other locations (represented by ovals) in S_{best} as shown by the red lines and black dashed lines. We prove that (1) $cost(T_{hs}) \leq cost(S_{best}) + 3\theta$ which is equivalent to prove $a' + b' + c' + d' + e' \leq a + b + c + d + e + 3 \times \theta$ since the dashed lines are common in both schedules.

We know $d' \leq b + c$, $e' < d + e$. Now we only need to show $a' + b' + c' \leq a + 3 \times \theta$. As shown in 5 (b), we can easily prove that $c' \leq a + \theta$ because the shortest path between x_k and x_{i+1} is no longer than than the schedule x_k, x_i, x_{i+1}. Because $b' \leq \theta$ and $c' \leq \theta$, we know $a' + b' + c' \leq a + 3 \times \theta$.

However, the hotspot algorithm may not use the same order of x_i, x_j, x_k as in the optimal solution as it is an arbitrary order, we now approve that (2) for any two hotspot-based schedule S_{hs} and $S_{hs'}$, $cost(S_{hs}) \leq cost(S_{hs'}) + (m+1)\theta$ where $m = 3$. Without loss of generality, let $S_{hs} = \ldots, x_{i-1}, x_i, x_j, x_k, x_{k+1} \ldots$ and $S_{hs'} = \ldots, x_{i-1}, x_j, x_k, x_i, x_{k+1} \ldots$. It is obvious that $d(x_{i-1}, x_i) \leq d(x_{i-1}, x_j) + \theta$ and $d(x_k, x_{k+1}) \leq d(x_i, x_{k+1}) + \theta$. Also $d(x_i, x_j) \leq d(x_j, x_k) + \theta$ and $d(x_j, x_k) \leq d(x_k, x_i) + \theta$. Adding the inequalities together, we have $cost(S_{hs}) \leq cost(S_{hs'}) + 4\theta$

Putting (1) and (2) together, we have $cost(S_{hs}) \leq cost(S_{best}) + (2m+1) \times \theta$ where $m = 3$. □

Because after we build the whole tree, we select the shortest schedule with hotspot $cost(S_{hsBest})$ and it is obvious that $cost(S_{hsBest}) \leq cost(S_{best}) + 2(m+1) \times \theta$.

When we consider the constraints, for S_{best} the corre-

sponding hotspot-based schedule with constraint may violate some constraints and thus does not exist. However, when the constraints of points of the best schedule are relaxed, the corresponding hotspot-based schedule will be found. We have the following theorem.

Theorem 3: $cost(S_{hs}) \leq cost(S_{best}) + 2(m+1) \times \theta$ where m is the number of points in the hotspot when constraints of all points in S_{best} is larger than $m\theta$.

Proof Sketch: Again we prove for $m = 3$ because of the ease of illustration. In Figure 5 (a), if (a, p, b, c, q, d, e) is a valid partial schedule with each node having at least 3θ slack time, then $(a', b', c', p, d', q, e')$ is a valid partial schedule.

For any point on p, the extra delay is $a' + b' + c' - a \leq 3 \times \theta$. For any point on q, the extra delay $a' + b' + c' - a + d' - (b + c) \leq a' + b' + c' \leq 3 \times \theta$. For x_{i+1}, the extra delay is $a' + b' + c' + d' + p + q - (a + b + c + d + p + q)$ which is proven in Theorem 2 as no larger than $3 \times \theta$. □

When θ is sufficiently small, we will likely to find a schedule that is upper bounded by the best schedule with a small additional time.

VI. Experimental Design

Data for the experiments is based on trips of 17,000 Shanghai taxis for one day (May 29, 2009); the dataset contains 432,327 trips. Each trip t includes the starting and destination coordinates $t.s$ and $t.e$ and the start time $t.time$ (i.e., the time at which the taxi picked up the passengers for the trip).

A simulation framework submits trip requests to the system in real-time based on the trips. Specifically, for each trip t, and trip request is initialized as $tr =< s_i = t.s, e_i = t.e >$, and tr is submitted at time $t.time$ in the simulator.

An instance of the route algorithm is associated with a vehicle. When a new trip request is received, the simulator trips the request with each vehicle and then chooses the vehicle returning the minimum time; the request is then assigned to that vehicle.

The simulation framework executes based on an undirected, weighted graph derived from and representing the Shanghai road network. This graph contains 122,319 vertices and 188,426 edges. The starting and destination trip coordinates are pre-mapped to the closest vertex in the graph. This may result in some inaccuracy if the coordinates are in the middle of a street or if the coordinates do not match with the road network data, but this inaccuracy is negligible. A vehicle is initialized to a random vertex in the city, and then follows a given route when there are customer(s) on board or, otherwise, follows the current road segment (at intersections, the next segment to follow is chosen randomly). We assume that speed in the road network is a constant 14 meters/second (approximately 48 kilometers/hour). Then, most computations are done in terms of distance instead of time (such as finding the path with shortest duration).

The framework is implemented in C++. We run the experiments on cluster nodes with an Intel Xeon X5550 (2.67GHz) processor. The simluation implementation is single-threaded, so only one core of the CPU is used. We limit the memory usage of each simulation process to three gigabytes.

To simulate the taxis, we need both the distance and routes (vehicles follow) between vertices in the road network. Computing shortest path on road networks has been widely studied (see [**?**] for an extensive review). A variety of techniques [**?**], such as A^*, Arc-flag (directing the search towards the goal), highway hierarchies (building shortcuts to reduce search space, transit node routing (using a small set of vertices to relay the shortest path computation), and utilizing spatial data structures to aggressively compress the distance matrix, have been developed. Recently, Abraham *et al.* [**?**] recently discovered that several of the fastest distance computation algorithms need the underlying graphs to have small *highway dimension*. Furthermore, they demonstrate the method with the best time bounds is actually a labeling algorithm [**?**]. We implement the state-of-art hub-labeling algorithm - a fast and practical algorithm to heuristically construct the distance labeling on large road networks, where each vertex records a set of intermediate vertices (and their distance to them) for the shortest path computation [**?**]. For the purposes of tracking taxi location, a second version of the road network is stored in memory in a weighted adjacency list structure without additional information.

However for large scale ridesharing, the shortest path algorithm is called very frequently and can be the bottleneck if not implemented efficiently. We observe the repeated calling follows a pattern that preserves locality. So, we implement two **LRU caches** using a single hash table, one storing up to ten million shortest distances and the other storing up to ten thousand shortest paths (separate caches are used because more distances can be stored in memory, and shortest distance is needed more often than shortest path). Both caches are indexed only by the starting and destination points in a distance or path computation call; this is accomplished by defining the index for two vertices s and e as $i = \text{id}(s) \cdot |V| + \text{id}(e)$, where id returns an integer representation for a vertex.

Parameter	Tested settings
Capacity	**4**
Constraints	5 min / 10%; **10 min / 20%**; 15 min / 30%; 20 min / 40%; 25 min / 50%
Number of servers	1,000; 2,000; 5,000; **10,000**; 20,000

TABLE I

Parameters for four-algorithm comparison.

A. Four Algorithm Comparison

We first compare kinetic tree algorithm with the branch and bound, brute-force, and mixed-integer programming algorithms under the dataset of 432,327 trips.

We choose three important parameters: capacity, waiting time and tolerance constraints, and number of taxis/servers. We first establish reasonable defaults for the parameters, and then proceed to modify the parameters one at a time to evaluate



Fig. 6. Results for changing number of customer requests (a), constraints (b), and number of servers (c). Default parameters are 10 min / 20% for the constraints, 10,000 servers, and a capacity of 4.

their effect. The defaults (bolded) and other tested settings are shown in Table I. Note that a waiting time constraint of 10 minutes corresponds to 8,500 meters.

To evaluate performance, we measure the average customer response time (ACRT), the average time required to complete the search for the minimum time needed to satisfy a new request. We further measure the average response time (ART), the average time needed to calculate the best route for a taxi to follow given its current state, for different request sizes. Depending on the number of requests need to be scheduled, the ART can change significantly (for example, a taxi with twenty current requests would have forty more points to schedule than one with no assigned requests). Thus, we calculate ART separately for different current request sizes and then compare to see the effect of the number of current requests on response time.

The default taxi capacity is set at four both to mimic real-world situations and because a higher capacity results in other algorithms not being able to finish executing within a reasonable time. Additionally, rather than testing lower capacities, we use ART to find the effect of different problem sizes on the efficiency of the algorithms.

Figure 6 shows the four-algorithm comparison. Figure 6 (a) shows the ART with different numbers of requests. Figures 6 (b) and (c) show the ACRT for varying constraints and fleet size, respectively. Generally, the brute-force and branch and bound algorithms exhibit roughly the same performance. The mixed-integer programming approach takes significantly more time, probably because of significant execution time used to initialize and preprocess each mixed-integer programming problem. The tree algorithm outperforms the other algorithms for all test cases, due to its incremental approach.

For a small number of taxis and a large number of customers already scheduled to the taxi, branch and bound outperforms brute-force. The reason is most likely that the pruning effect of branch and bound is more important when the shortest route calculations have more customer requests, because the problem size is larger. When the problem size is small, the fast initialization of the brute-force algorithm is preferable; branch and bound, on the other hand, has to first calculate the minimum edges for each of the vertices in the complete graph of pickup and dropoff points that it uses.

For the default parameters, the execution time of the branch-and-bound and brute-force algorithms are almost identical, while the mixed-integer programming is approximately 20 times slower. The tree algorithm, on the other hand, is almost two times faster than the branch-and-bound algorithm. Similar magnitude execution time differences are seen for other parameters.



Fig. 8. ART for four customer requests when changing constraints (a) and number of servers (b). Default parameters are 10 min / 20% for the constraints, 10,000 servers, and a capacity of 4.

In Figure 8, we show ART when shortest routes are be-



Fig. 7. Results with tree algorithms for different numbers of customer requests (a), changing constraints (b), and changing number of servers (c). Default parameters are 10 min / 20% for the constraints, 2,000 servers, and a capacity of 6 ((a) shows ART in different cases for these parameters).

ing calculated for four customer requests to get an idea of performance of larger sizes. These are graphed as constraints or number of servers increase. For constraints, the ART gradually increases as the constraints become looser. This makes sense because more feasible combinations that have to be considered. Additionally, the brute-force appears to be less influenced by this trend, probably because the brute-force anyway enumerates each permutation(the constraints still does effect its ART because it can stop earlier on average when checking the feasibility of each permutation).

The increasing number of servers appears to have little effect on the tree algorithm, but for the other three algorithms, the ART clearly decreases. This is most likely because with more servers, most of the cases where there are four passengers occur when the pickup and dropoff points of the passengers are not as clustered: there will often be an empty server close to a server with several passengers, and it would get the next request. Because the pickup and dropoff points are farther apart, there are less combinations and the execution time is lower. On the other hand, when there are few servers, the servers are spread farther apart, meaning that it is more likely for a single server to handle several clustered requests.

B. Comparing Tree Algorithms

We further evaluate different versions of our tree algorithm: basic tree algorithm, the slack time algorithm, and the hot-spot clustering algorithm (which also uses slack time).

Parameter	Tested settings
Capacity	3; 4; 5; **6**; 7; 8; 12; 16; unlimited
Number of servers	500; 1000; **2000**; 5,000; 10,000
Constraints	5 min / 10%; **10 min / 20%**; 15 min / 30%; 20 min / 40%; 25 min / 50%

TABLE II
PARAMETERS FOR TREE ALGORITHM COMPARISON.

We set a default capacity of six because we find that the tree algorithms are able to solve larger problems than the other approaches. The incremental nature of the tree algorithms and improvements in the hot-spot clustering algorithm allows us to explore the effect of an unlimited capacity (for most of the other algorithms, we find that this leads to too great a search space), which gives an idea of what the maximum achievable ridesharing is. The parameters we use for evaluating the tree algorithms are shown in Table II, with the bolded values being the default settings.

We now evaluate the performance of the slack time and hot-spot clustering improvements that we make to the tree algorithm. Figure 7 shows these results. The slack-time algorithm is faster than the basic tree algorithm except when the number of servers is 10,000, the number of customer requests is 6, or the constraints are at 20 min / 40%; these cases are examined more closely in Figure 9. Slack-time achieves a maximum time saving of over 32% compared to the basic tree algorithm when the constraints are at the tighest level tested, 5 min / 10%. For the default parameters, it yields savings of approximately 18%. So, the slack-time does yield a relatively significant improvement in time, especially when constraints are tight so that many branches in the tree are infeasible.

Figure 9 presents results similar to those in Figure 8, but for the tree algorithms. Most prominent in the graphs is the steep increase in ART for tight constraints and large capacities with the basic and slack-time tree algorithms; this is opposite to the results in Figure 8. It can be explained, however, by the increased capacity that we use. In both cases where the ART is large, it is relatively rare for a server to have six passengers: typically, there would either be another server with less passengers available to handle the request or the constraints would be too tight to allow so many passengers. So, when the server is able to get six passengers, it is most likely because the pickup/dropff points are very close to each other. In these cases, the short distance between the points creates a large number of feasible combinations. Although these cases would also appear for looser constraints and smaller numbers of servers, the ART is an average, and other six-passenger-cases that do not create a large number of combinations would be much more common. This also explains why the hot-spot clustering algorithm is not affected by the trend. The slack-time tree algorithm is faster than the basic tree algorithm because slack time only reduces execution time when there are many infeasible branches that can be pruned.

Additionally, like in Figure 8, the ART in Figure 9 increases



Fig. 9. ART for six customer requests when changing constraints in (a) and number of servers in (b). In (c), tree-algorithm ACRT for different capacities. "unlim" indicates unlimited capacity. Only hotspot clustering algorithm can complete for unlimited capacity. Default parameters are and a capacity of 6, 10 min / 20% for the constraints and 2,000 servers.

gradually with looser constraints starting from the 10 min / 20% parameters because looser constraints also allow more feasible combinations.

Figure 9 (c) shows the ACRT results for different capacities. The ACRT breaks off for each algorithm when it can no longer finish in a reasonable time or exceeds the imposed memory limit of three gigabytes. The hot-spot clustering algorithm is the only one that is able to finish the simulation program with a capacity greater than seven, and also for unlimited capacity (marked as unlim in the figure).

From this figure, we can see that while the basic and slack-time tree algorithms are unable to continue processing when the problem sizes become too large, the hot-spot clustering algorithm is scalable to higher capacities. This also confirms our hypothesis that the biggest issue for unlimited capacity is situations where a large number of passengers wish to depart from a single point; hot-spot clustering combines these points in the tree.

The maximum number of passengers at unlimited capacity in a single server is 17, while the average is 1.7 (this is with the default parameters, so the number of servers is two thousand). The average in the top 20% filled servers is a bit higher than 3.9. This indicates that the majority of vehicles in a server fleet should be five-person cars (with one of the five seats taken by the driver), but for some requests larger vehicles are needed.

VII. Related Work

Our work is related to nearest neighbor (NN) search on moving objects over road networks. Early work on nearest neighbor search on road networks focuses on data models that are easy to implement and serve as a foundation for NN queries [14]. Later research has focused on continuous monitoring of nearest neighbors (NN) in highly dynamic scenarios, where the queries and the data objects move frequently on a road network [15]. A recent paper addresses the problem of monitoring the k nearest neighbors to a dynamically changing path in road networks. Given a destination where a user is going to, this new query returns the k-NN with respect to the shortest path connecting the destination and the users current location [16]. Guting *et. al.* proposed algorithms to find the k nearest neighbors to m_q within D for any instant of time within the lifetime of m_q given a set of moving object trajectories D and a query trajectory m_q [17]. Nearest neighbor query on road network is only the minor step in the ridesharing system that can help to filter the initial set of candidate taxis.

The *trip grouping* algorithm [5] groups "closeby" cab requests using a set of heuristics. Requests are queued for a user given waiting time to be scheduled. The heuristics include grouping requests upon expiration, estimation combination saving using pairwise request combination gain, and greedy grouping. The trip grouping algorithm is then expressed as a continuous stream query and optimized by space partitioning and parallelization. This method is heuristic-based and does not provide waiting and riding time service guarantee as our method does.

In operation research, early research on this problem mostly focuses on a single vehicle and a static scenario where the set of requests are known ahead of time. This is unrealistic for large scale and ad-hoc services such as a taxi service. The problem is, unsurprisingly, NP-hard. Only problems with small sizes can be solved to optimality. Exact dynamic programming algorithms have been developed [18]. Note that the problem without a deadline can be considered as the special case of the problem with a deadline where the deadline is infinite. Once the fixed deadline is given, we can construct subproblems using these deadlines, and thus dynamic programming can be employed. However, in our case, since the maximal waiting time and the service level are two separate constraints, each trip request can be enforced with a fixed completion deadline. Thus, the dynamic programming approaches can not be applied to our problem. We also note that our problem can be considered more general than the fixed deadline problem. Given a fixed deadline t, the maximal waiting time can be defined as $w = t - (1 + \epsilon)d(s, e)$. Thus, our algorithm can also be used for the fixed deadline problem.

In a dynamic single vehicle DARP problem, requests come in real time and a server has to make decisions on-line [6]. In the problems without deadline, the objectives are to minimize *makespan* (time to finish the last request) or the *average completion time*. *Competitive ratio* is a standard tool to measure the effectiveness of a dynamic DARP algorithm.

An on-line algorithm A is called $c - competitive$ if for any instance δ, the cost of A on δ is at most c times the offline optimum on δ. This is assuming an optimal solution is available which is false for modern large scale scheduling problem we are addressing .

This paper deals with the multiple servers, dynamic (i.e. real-time) DARP with deadlines. When deadline is involved, the objectives are three folds: (1) real-time response; (2) minimize average completion time; (3) maximize requests served. The most related work is the two-phase insertion technique [19].

The single vehicle problems are typically solved to optimality by a branch-and-bound algorithm which may incur exponential time complexity [7]. The state-of-the-art Branch-and-cut (*BaC*) algorithm [8] formulates the multiple server version of this problem using mixed-integer programing and a branch-and-cut solution. *BaC* can find exact solutions for small to medium size instances (4 vehicle and 32 requests on a moderate PC for tens to hundreds of minutes). It assumes all vehicles and requests are available ahead of time which is not realistic for a dynamic taxi service of thousands of vehicles serving through out the day. Nevertheless, the solution can be adopted to accommodate the attempts of combining new requests with existing routes of vehicles. We compare our kinetic tree based approach to a branch-and-bound approach and a mixed integer programing approach in this paper.

VIII. Conclusion

In this paper, we formulate and propose a kinetic tree algorithm with optimizations to dynamically match real-time trip requests to servers in a road network to allow ridesharing. The proposed algorithm outperforms commonly used approaches including branch and bound and mixed-integer programing, as shown by expriments on a large taxi dataset. In the future, we would like to consider uncertainty issues in scheduling; this is very important and may be a major road block in achieving large scale ridesharing.

References

[1] K. Ghoseiri, A. Haghani, and M. Hamedi, "Real-time rideshare matching problem," *Final Report of UMD-2009-05, U.S. Department of Transportation*, 2011.

[2] J. F. Dillenburg, O. Wolfson, and P. C. Nelson, "The intelligent travel assistant," in *The IEEE 5th International Conference on Intelligent Transportation Systems*, 2002, pp. 691–696.

[3] TICKENGO, "Tickengo," http://tickengo.com.

[4] C. Stach and A. Brodt, "vhike - a dynamic ride-sharing service for smartphones," in *Mobile Data Management*, 2011, pp. 333–336.

[5] G. Gidofalvi, T. B. Pedersen, T. Risch, and E. Zeitler, "Highly scalable trip grouping for large-scale collective transportation systems," in *Proceedings of the 11th international conference on Extending database technology: Advances in database technology*, ser. EDBT '08, 2008, pp. 678–689.

[6] E. Feuerstein and L. Stougie, "On-line single-server dial-a-ride problems," *Theor. Comput. Sci.*, vol. 268, no. 1, pp. 91–105, Oct. 2001.

[7] A. Colorni and G. Righini, "Modeling and optimizing dynamic dial-a-ride problems," *International Transactions in Operational Research*, vol. 8, no. 2, pp. 156–166, 2001.

[8] J.-F. Cordeau, "A branch-and-cut algorithm for the dial-a-ride problem," *Oper. Res.*, vol. 54, no. 3, pp. 573–586, 2006.

[9] Y. Tao, D. Papadias, and J. Sun, "The tpr*-tree: an optimized spatio-temporal access method for predictive queries," in *Proceedings of the 29th international conference on Very large data bases*, 2003, pp. 790–801.

[10] M. F. Mokbel, X. Xiong, and W. G. Aref, "Sina: scalable incremental processing of continuous queries in spatio-temporal databases," in *Proceedings of the 2004 ACM SIGMOD international conference on Management of data*, 2004, pp. 623–634.

[11] C. S. Jensen, D. Lin, and B. C. Ooi, "Query and update efficient b+-tree based indexing of moving objects," in *Proceedings of the Thirtieth international conference on Very large data bases*, 2004, pp. 768–779.

[12] B. Kalantari, A. V. Hill, and S. R. Arora, "An algorithm for the traveling salesman problem with pickup and delivery customers," *European Journal of Operational Research*, vol. 22, no. 3, pp. 377–386, 1985.

[13] M. Desrochers and G. Laporte, "Improvements and extensions to the miller-tucker-zemlin subtour elimination constraints." *Operations Research Letters*, vol. 36, no. 10, pp. 27–36, 1991.

[14] C. S. Jensen, J. Kolářvr, T. B. Pedersen, and I. Timko, "Nearest neighbor queries in road networks," in *Proceedings of the 11th ACM international symposium on Advances in geographic information systems*, 2003, pp. 1–8.

[15] K. Mouratidis, M. L. Yiu, D. Papadias, and N. Mamoulis, "Continuous nearest neighbor monitoring in road networks," in *Proceedings of the 32nd international conference on Very large data bases*, ser. VLDB '06, 2006, pp. 43–54.

[16] Z. Chen, H. T. Shen, X. Zhou, and J. X. Yu, "Monitoring path nearest neighbor in road networks," in *Proceedings of the 2009 ACM SIGMOD International Conference on Management of data*, ser. SIGMOD '09, 2009, pp. 591–602.

[17] R. H. Güting, T. Behr, and J. Xu, "Efficient k-nearest neighbor search on moving object trajectories," *The VLDB Journal*, vol. 19, no. 5, pp. 687–714, Oct. 2010.

[18] H. Psaraftis, "An exact algorithm for the single-vehicle many-to-many dial-a-ride problem with time windows," *Transportation Science*, vol. 17, no. 3, pp. 351–357, 1983.

[19] L. Coslovich, R. Pesenti, and W. Ukovich, "A two-phase insertion technique of unexpected customers for a dynamic dial-a-ride problem," *European Journal of Operational Research*, vol. 175, no. 3, pp. 1605–1615, 2006.